



# Slide Latch HIGH HARDNESS

**NEW**

## SLK-8-HH

Rated to carry a weight up to 8 pounds. 100% interchangeable with SLK-8A



**BODY**

**LOCK**

SKD 11 HRC 56-58

### INSTALLATION - LOCK

**OPTION A  
MACHINED INTO SLIDE**

MIN .375

R .020

.054

90°

R .030

**OPTION B  
LOCK INSERT**

∅ .502

.150

.400

TAP 2-56 x .250 DEEP

.110

.152

.150

### INSTALLATION - BODY

∅ .502

∅ .500

BOTTOM MOUNTING  
C'BORE FOR 4-40

.302

.300

.150

TAP 2-56 .250 DEEP

### DESIGN GUIDELINES

FULL STROKE  
MINUS -.020

SEE VIEW A

VIEW A

**NOTE:** Set angle pin to release .020 from full stroke. Striker will snap to full stroke to assure re-entry clearance of angle pin

## SLK-25-HH

Rated to carry a weight up to 25 pounds. 100% interchangeable with SLK-25A

**NEW**

**BODY**

**LOCK**

SKD 11 HRC 56-58

TAPPED 10-32 FOR BOTTOM MOUNTING  
C'BORE 6-32 SHCS FOR TOP MOUNTING

1.490

1.100

1.490

.620

.620

.310

.498

.100

.249

LARGE LEAD IN  
TAPER & RADIUS

### INSTALLATION - LOCK

**OPTION A  
MACHINED INTO SLIDE**

MIN .750

R .047

45°

.105

90°

R .083

**OPTION B  
LOCK INSERT**

.025-.027

.313

1.500

.875

1.100

.313R

TAP 8-32  
.300 DEEP

.135

.252

.125

.250

### INSTALLATION - BODY

.313

1.500

.502

.500

BOTTOM MOUNTING  
C'BORE FOR 10-32

.027

.025

1.100

TAP 6-32  
.300 DEEP

### DESIGN GUIDELINES

FULL STROKE  
MINUS -.030

SEE VIEW A

VIEW A

**NOTE:** Set angle pin to release .030 from full stroke. Striker will snap to full stroke to assure re-entry clearance of angle pin



# Slide Latch

## MACHINING DATA

**NEW**

Slide-Latch model SLK-50HH is rated to carry a weight of up to 50 pounds. Ideal for die cast mold slide applications. Multiple Slide-Latches can be easily machined and mounted in mold slides for higher load retentions.

